

ECGR 4101/5101/6090, Fall 2004: Lab 5

Interrupts I/O

Learning Objectives

This lab will introduce you to using interrupts to perform serial I/O available on the MSV30262-SKP board, and new C programming concepts.

General Information

The general steps for this lab are:

1. Generate a new project. Name your new project Lab5.
2. Modify the main.c file and include the appropriate files. Include commenting along the way.
3. Program the lab. Don't forget the necessary include files to get the correct functionality.
4. Compile the code into an .x30 file, and load onto the board.
5. Test the program and repeat sets 4 and 5 until the program works as required.
6. Write your lab report.
7. Demonstrate for a TA and turn in your report.

Prelab Activity

You may use the PCs in Smith 347 or your own PC to do this lab experiment. The machines in Smith 347 already have the software tools loaded.

1. Write the pseudo code for this lab

Laboratory Assignments

In this lab you will be performing serial communications with interrupts. This lab will use the on-board UART to communicate between two boards. The LED's will be used for signaling and the LCD can be used to display debugging information. This lab must be demonstrated to the TA.

You will be expected to respond to several different commands. All valid commands will be transmitted in uppercase. The commands that are valid are R, Y, and G toggle the respective red, yellow, and green LEDs. All other characters should be considered invalid and should trigger the invalid response.

1. The program should use queues to receive and transmit characters.
2. The main program should check the queue for characters.
3. If a character is received it should be checked for validity.
4. If the command is valid the program should act accordingly.
5. Once the command has been processed the program should poll for the next command.

Steps

1. Follow the steps given in lab 2 for generating a new project.
2. Create the main.c file and include the appropriate files.
3. Build your program slowly, testing along the way. Perform compiles and solve each requirement one at a time.
4. Continue to build and test the program until all of the requirements have been met. Did we mention you should write your comments as you progress, not at the end?
5. If you run into problems, use the break point functionality of KD30 to step through the code until you find the problem.
6. Once all the requirements have been met, ensure that everything works.
7. Finish lab write-up and demonstrate for a TA.

Requirements

- Req. 1 – The code generated is written in C for the SKP16C26.
- Req. 2 – The code is well commented and easy to follow
- Req. 3 – The serial communications should operate at 1200 baud, even parity, 8 data bits, one stop bit.
- Req. 4 – The two student boards will be connected via the UART0 transmit, receive, and ground pins. The transmit pin on one board will be connected to the receive pin on the other board.
- Req. 5 – Both boards will wait for a button press on its own board or a byte to be received from the other attached board. These activities should be generated via an interrupt.
- Req. 6 – If “R” is received from the other board, then the Red LED is inverted on the board.
- Req. 7 – If “Y” is received from the other board, then the Yellow LED is inverted on the board.
- Req. 8 – If “G” is received from the other board, then the Green LED is inverted on the board.
- Req. 9 – If SW1 is pressed and an interrupt generated, the Red LED is inverted on the board and the character “R” is sent to the other board.
- Req. 10 – If SW2 is pressed and an interrupt generated, the Yellow LED is inverted on the board and the character “Y” is sent to the other board.
- Req. 11 – If SW3 is pressed and an interrupt generated, the Green LED is inverted on the board and the character “G” is sent to the other board.
- Req. 12 – Queues will be used to transmit and receive characters.
- Req. 13 – Once a command is processed the program returns to checking for a character in the queue.
- Req. 14 – The color of the LEDs on both boards must always match.

Lab Report

Turn in a hard copy of the code you wrote and a printout of the map file. Also include in your lab report observations and procedure like the following:

The general learning objectives of this lab were . . .

The general steps needed to complete this lab were . . .

Some detailed steps to complete this lab were . . .

1. Step one

2. *Step two*

3.

Code generated for this lab...

Some important observations while completing/testing this lab were . . .

In this lab we learned